

■ Specification

Model	Unit	BT-3S	BT-4S
INJECTION PART			
SCREW DIAMETER	mm	28	45
THEORETIC INJECTION VOLUME	cm ³	86	223
PLASTICIZING CAPACITY (PET)	Kg/hr	25	64
SCREW ROTATION SPEED	r.p.m.	0~100	
CLAMPING FORCE	ton	40	60
OPENING STROKE	mm	300	
BLOWING PART			
BLOW MOLD CLAMPING FORCE	ton	20	30
BLOW MOLD OPENING STROKE	mm	120	140
STRETCH STROKE	mm	300	
ELECTRICAL PART			
ELECTRIC POWER (PUMP)	Hp/KW	25 / 18.5	40 / 29.7
TABLE SERVO MOTOR	Hp/KW	1.0 / 0.75	2.0 / 1.5
HEATER	Hp/KW	12.6 / 9.5	15.6 / 11.6
HYDRAULIC PART			
OIL TANK CAPACITY	liter	250	260
SYSTEM MAX. PRESSURE	Kg/cm ²	140	
COOLING WATER CAPACITY	l/min	400	600
AIR PART			
PROCESS AIR PRESSURE	Kg/cm ²	9	

Remarks: a) Specifications are subject to change without notice
b) Special models are available; please feel free to contact us.

BLOWTECH Blowplas Technology Co Ltd

No.182-29, Sec.1 Chungshan Rd., Hsinchuang Dist., New Taipei City 242, Taiwan

Tel:+886-2-8522-2655

Fax:+886-2-8522-2676

Http://www.blowtech.com.tw

Email:info@blowtech.com.tw

Simple • Reliable